Full Automatic, LCD Screen Display Rockwell Hardness Tester HRA3000 AZFM

Product Details:

Place of Origin:	**China**
Brand Name:	**HUATEC**
Model Number:	**HRA3000 AZFM**

Payment & Shipping Terms:

Minimum Order Quantity:	**1 SET**
Packaging Details:	**Wooden Case**
Delivery Time:	**7-10 days**
Payment Terms:	**TT, L/C, Western Union**

Chat Now

Large Image : Full Automatic, LCD Screen Display Rockwell Hardness Tester HRA3000 AZFM

Detailed Product Description

Full Automatic, LCD Screen Display Rockwell Hardness Tester HRA3000 AZFM
Detailed Product Description
Full Automatic Rockwell Hardness Tester
1. The Most advanced
2. Full Automatic
3. Large LCD Screen display
4. Passed CE
Main Features:
Model HRA3000 AZFM Full Automatic Rockwell Hardness Tester is fully automatic hardness tester, put the sample, the process of automatic testing, hardness press of a button
Main function:
Automatic increase in the sample (no height limit)
The initial test force applied automatically
The main test force applied automatically
Automatic measurement of hardness values
Automatic digital display hardness values
Measurable HRA, HRB, HRC, HRD, HRE, HRF, HRG, HRH, HRK
Can automatically correct the measurement error
Hardness automatic conversion

China Good Quality Ultrasonic Flaw Detector Supplier. Copyright © 2011 - 2017 huatecgroup.com. All Rights Reserved.

Built-in printer to print the test results

Usage Range:

Hardened steel, the tempering steel, steel, steel rolling, annealing cold malleable iron, aluminum alloy, copper and so on.

Technical Specifications:

Model	HRA3000 AZFM
Conversion Scale	Superficial Rockwell, Brinell, Vickers
Indication of Hardness Value	Large LCD screen display
Max Height of Specimen	175mm, Heighten: 400mm
Data output	Inside Printer, RS-232
Net weight	About 65Kg
Power supply	AC220V
Overall Dimension (mm)	520*240*720
Duration time	2-60s
Carried Standard	GB/T230.1 Chinese Standard, GB/T230.2 Chinese Standard, JJG112 Inspection Rule, ASTM Standard
Distance of Indenter to outer wall	160mm
Speed of Increase the sample	3mm/s
Preliminary Testing force	10kgf(98.07N)
Testing force	60kgf(588N) 100kgf(980N) 150kgf(1471N)
Rockwell Scale	HRA,HRB,HRC,HRD,HRE,HRF,HRG,HRH,HRK
Hardness measuring range	HRA:20-88 HRB:20-100 HRC:20-70 HRD:40-77 HRF:60-100 HRG:30-94 HRH:80-100 HRK:40-100

Standard Accessories:

Item	Quantity	Item	Quantity
Diamond Rockwell Indenter	1	Diameter 1.5875mm Ball Indenter	1
Hardness block (HRC High Low 2, HRB 1)	3	Large, Medium, “V” shaped Testing Table	Each 1
Weights(A,B,C)	Each 1	Plastic Dustproof cover	1
Manual	1	Product certificate	1

China Good Quality Ultrasonic Flaw Detector Supplier. Copyright © 2011 - 2017 huatecgroup.com. All Rights Reserved.